PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : G01C 15/00

A1

(11) International Publication Number: WO 99/60335

(43) International Publication Date: 25 November 1999 (25.11.99)

(21) International Application Number: PCT/GB99/01361

(22) International Filing Date: 17 May 1999 (17.05.99)

(30) Priority Data:
9810405.2 15 May 1998 (15.05.98) GB

(71) Applicant (*for all designated States except US*): MEASUREMENT DEVICES LIMITED [GB/GB]; Silverburn Crescent, Bridge of Don, Aberdeen AB23 8EW (GB).

(72) Inventor; and
(75) Inventor/Applicant (*for US only*): BALL, Stephen, Leslie [GB/GB]; Knockhill Farm, Strachan, By Banchory AB31 6LL (GB).

(74) Agent: MURGITROYD & COMPANY; 373 Scotland Street, Glasgow G5 8QA (GB).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
With international search report.

(54) Title: SURVEY APPARATUS

(57) Abstract

A survey apparatus and method is provided which allows a user of the apparatus to view a target area on a screen using a camera. The image on the screen can be captured and a target within the screen selected to measure the distance or range to the target using a laser range finder.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

"Survey Apparatus"

The present invention relates to a survey apparatus and method.

Conventional survey equipment typically measures the distance, bearing and inclination angle to a target (such as a tree, electricity pylon or the like) or a target area, with reference to the position of a user. Such conventional equipment does not allow the user to produce an image of the target which can be used to measure heights and distances between objects within the target area.

In addition, conventional sighting devices which are used to select a target to be surveyed often result in false surveys being made as the target is often not correctly identified.

According to a first aspect of the present invention there is provided a survey apparatus comprising a range finder, a camera, a processor capable of processing image and range signals, wherein the camera facilitates aiming of the range finder.

According to a second aspect of the present invention there is provided a method of measuring the range to a target, the method comprising the steps of

providing a camera to view a target area;

providing a range finder;

using the camera to produce an image of the target area;

selecting the target within the target area;

generating horizontal and vertical angles between a reference point and the target; and

moving the range finder, if required, through the generated horizontal and vertical angles to measure the range to the target.

The camera is preferably a video camera, and more preferably a digital video camera. The camera may comprise a charge-coupled device (CCD) video camera. Alternatively, the camera may comprise a digital image camera. The apparatus typically includes a display device to allow a user to view a target area using the camera. The display device typically comprise a VGA monitor. Alternatively, the display device may comprise a VGA eyepiece monitor, such as a liquid-crystal display (LCD) or flat panel display. This offers the advantage that an image of the target may be viewed by the user to ensure that the correct target has been selected. Also, the survey apparatus may be operated remotely using the camera to view the target area.

The processor typically comprises a computer.

The range finder is typically a laser range finder. Optionally, the laser range finder is bore-sighted with the camera. This, in conjunction with the monitor used to identify the target area, offers the advantage that

the user can be sure that the target area he has selected will be captured by the camera, and that the target area can be viewed remotely of the apparatus. In addition, if the camera is bore-sighted with the range finder, then any subsequent calculations made by the image processor do not require an offset between the camera and the range finder to be considered.

The apparatus typically calculates the range to specified points and incorporates such distance measurements into the image displayed on a screen.

The apparatus preferably includes a pan and tilt unit for panning and tilting of the range finder and/or camera. The pan and tilt unit typically comprises a first motor for panning of the range finder and/or camera, and a second motor for tilting of the range finder and/or camera. The pan and tilt unit typically includes first and second digital encoders for measuring the angles of pan and tilt. The first and second motors are typically controlled by the processor. The outputs of the first and second encoders is typically fed to the processor. This provides a feedback loop wherein the motors are operated to pan and tilt the range finder and/or camera through the generated horizontal and vertical angles. The encoders may then be used to check the angles to ensure that the range finder and/or camera were panned and tilted through the correct angles.

The image is preferably digitised, wherein the image comprises a plurality of pixels. The reference point is typically a pixel within the target area, and may be a centre point of the target area or one of the corners. The target is typically selected by selecting a pixel within the target, using, for example, a mouse

pointer. This produces x and y coordinates for the target pixel.

Optionally, the survey apparatus includes a compass and an inclinometer and/or gyroscope. The compass is typically a digital fluxgate compass. These allow the bearing and angle of inclination to the target to be measured. The signals from the compass, inclinometer and/or gyroscope are preferably digitised to provide data to the processor. The bearing and/or angle of inclination to the target can be displayed on the screen.

Optionally, the survey apparatus further includes a position fixing system for identifying the geographical position of the apparatus. The position fixing system is preferably a Global Positioning System (GPS) which typically includes a Differential Global Positioning System (DGPS). This provides the advantage that the approximate position of the apparatus can be recorded (and thus the position of the target using the measurements from the range finder and compass, where used). The GPS/DGPS typically facilitates the time of the survey to be recorded. The signal from the GPS is typically digitised to provide data to the processor.

The survey apparatus is typically mounted on a mounting device. The mounting device typically comprises a tripod stand. The apparatus can optionally be mounted on an elevating platform, telescopic elevating tube, telescopic arm, robotic arm or the like. This provides the apparatus with a larger viewing area. The elevating platform or the like is typically capable of 360° rotation. This provides a complete viewing range.

The apparatus allows data gathering from within a

vehicle to construct a digital terrain model of the terrain surrounding the vehicle.

The method typically comprises any one, some or all of the further steps of

obtaining a focal length of the camera;

obtaining a field of view of the camera;

calculating the principal distance of the camera;

obtaining the horizontal offset and vertical offset between an axis of the camera and an axis of the laser;

calculating the horizontal and vertical offsets in terms of pixels;

calculating the difference between the horizontal and vertical offsets in terms of pixel and the x and y coordinates of the target pixel; and

calculating the horizontal and vertical angles.

Optionally, the method typically includes one, some or all of the further steps of

instructing the pan and tilt unit to pan and tilt the range finder and/or camera through the vertical and horizontal angles;

measuring the horizontal and vertical angles using the encoders;

verifying that the angles through which the range finder and/or camera are moved is correct;

obtaining horizontal and/or vertical correction angles by subtracting the measured horizontal and vertical angles from the calculated horizontal and vertical angles;

adjusting the pan and tilt of the range finder and/or camera if necessary; and

firing the range finder to obtain the range to the target.

Embodiments of the present invention shall now be described, with reference to the accompanying drawings, in which:-

Fig. 1 is a schematic representation of a image capture and laser transmitter and receiver unit in accordance with, and for use with, the present invention;

Fig. 2 shows schematically a first embodiment of survey apparatus;

Fig. 3 shows an exploded view of the survey apparatus of Fig. 2 in more detail;

Fig. 4 shows a simplified schematic illustration of a digital encoder;

Fig. 5 schematically shows the survey apparatus of Figs 2 and 3 in use;

Fig. 6 is a schematic representation of the display produced on a computer screen of a freeze frame image produced by a digital camera;

Fig. 7 is a simplified schematic diagram of inside a digital camera;

Fig. 8 is a simplified diagram illustrating how a principal distance (PD) may be calculated;

Fig. 9 is a simplified diagram illustrating the offset between the laser and the camera in use;

Fig. 10 is a schematic representation illustrating a horizontal offset H_{offset} outwith the camera;

Fig. 11 is a schematic representation illustrating a horizontal distance l_x in terms of pixels, corresponding to H_{offset}, within the camera;

Fig. 12 is a simplified diagram of a freeze frame image showing an object;

Fig. 13 is a schematic representation illustrating the relationship between a horizontal distance d_x, a principal distance PD and an angle θ;

Fig. 14 is a schematic representation of a screen image of a target overlayed with range, bearing

and inclination information;

Fig. 15a is a schematic representation of a vehicle provided with an elevating arm and survey apparatus showing the position of the apparatus when the vehicle is moving;

Fig. 15b is a schematic representation of the vehicle of Fig. 15a with the apparatus deployed on the arm;

Fig. 15c is a schematic representation of the vehicle of Figs 15a and 15b on a slope with the apparatus deployed on the arm;

Figs 16a and 16b are respective rear and side views of the survey apparatus deployed on the arm;

Fig. 17 is an exemplary screen shot of an area which has been surveyed using the survey apparatus;

Figs 18a and 18b are respective side and plan elevations of the vehicle of Figs 15a to 15c illustrating the survey apparatus being used to profile the ground in front of the vehicle;

Figs 19a and 19b are side and plan views of the profile of the ground in front of the vehicle which is displayed for a user of the apparatus;

Fig. 20 illustrates a head-up display used by the driver of the vehicle, the display being generated by the survey apparatus;

Fig. 21 illustrates calculating the height difference between two points A and B using the survey apparatus;

Fig. 22 illustrates calculating the height and distance between two points A and B using the survey apparatus; and

Fig. 23 illustrates using the survey apparatus to profile a surface.

Referring to the drawings, Fig. 1 shows a schematic

representation of an image capture and laser transmitter and receiver unit 10 for use with the present invention. Unit 10 includes a laser 12 (which forms part of a laser range finder) which generates a beam of laser light 14. The laser 12 is typically an invisible, eyesafe, gallium arsenide (GaAs) diode laser which emits a beam typically in the infra-red (IR) spectrum. The laser 12 is typically externally triggered and is designed to measure up to 1000 metres or more to reflective and non-reflective targets. Any particular type of laser 12 may be used and the present invention is not limited to the particular embodiment shown.

The beam 14 is reflected by a part-silvered prism 16 in a first direction substantially perpendicular to the direction of the initial beam 14, thereby creating a transmit beam 18. The transmit beam 18 enters a series of transmitter optics 20 which collimates the transmit beam 18 into a target beam 22. The target beam 22 is reflected by a target (schematically shown in Fig. 1 at 24) and is returned as a reflected beam 26. The reflected beam 26 is collected by a series of receiver optics 28 and directs it to a laser light detector 30. The axes of the transmit and receiver optics 20, 28 are calibrated to be coincident at infinity.

Signals from the detector 30 are sent to a processor (not shown) which calculates the distance from the apparatus 10 to the target 24 using a time-of-flight principle. Thus, by dividing the time taken for the light to reach the target 24 and be reflected back to the detector 30 by two, the distance to the target 24 may be calculated.

Bore-sighted with the laser 12 (using the part-silvered

prism 16) is a digital video camera 32. The camera 32 is preferably a complementary metal-oxide silicon (CMOS) camera which is formed on a silicon chip. The chip generally includes all the necessary drive circuitry for the camera 32. It should be noted that the camera need not be bore-sighted with the laser. In this case, the transmit laser beam 22 will be offset in the x and/or y directions from the centre of the picture taken by the camera 32. The offsets can be calculated and the survey apparatus calibrated (using software) to take into account the offsets, as will be described.

The transmit optics 20 serve a dual purpose by also acting as a lens for the camera 32. Thus, light which enters the transmit optics 20 is collimated and directed to the camera 32 (shown schematically at 34) thereby producing an image of the target 24 at the camera 32. The image which the camera 32 receives is digitised and sent to a processor (not shown). It should be noted that a separate lens may be used for the camera 32 if required.

Referring now to Figs 2 and 3, Fig. 2 shows schematically a first embodiment of survey apparatus 100 mounted for movement in x and y directions, and Fig. 3 shows an exploded view of the survey apparatus 100 of Fig. 2 in more detail.

Referring firstly to Fig. 2, the image capture and laser transmitter and receiver unit 10 (Fig. 1) is typically mounted within a casing 50. The casing 50 is typically mounted to a U-shaped yoke 52, yoke 52 being coupled to a vertical shaft 54. Shaft 54 is rotatably mounted to facilitate rotational movement (indicated by arrow 56 in Fig. 2) of the casing 50 in a horizontal

plane (indicated by axis 58) which is the x-direction. The rotational movement of the shaft 54 (and thus the yoke 52 and casing 50) is controlled by a motor 60 coupled to the shaft 54, typically via a gearbox (not shown in Fig. 2). The operation of the motor 60 is controlled by the computer.

The angle of rotation of the casing 50 in the horizontal plane (ie the x-direction) is measured accurately by a first digital encoder 62, attached to the shaft 54 in a known manner, which measures the angular displacement of the casing 50 (and thus the transmit laser beam 22) in the x-direction.

Similarly, the yoke 52 allows the casing 50 (and thus the transmit laser beam 22) to be displaced in the y-direction as indicated by arrow 64. The casing 50 is mounted to the yoke 52 via a horizontal shaft 66. Shaft 66 is rotatably mounted to facilitate rotational movement (indicated by arrow 64 in Fig. 2) of the casing 50 in a vertical plane (indicated by axis 68) which is the y-direction. The rotational movement of the shaft 66 (and thus the yoke 52 and casing 50) is controlled by a motor 68 coupled to the shaft 56, typically via a gearbox (not shown in Fig. 2). The operation of the motor 66 is controlled by the computer.

The angle of rotation of the casing 50 in the vertical plane (ie the y-direction) is measured accurately by a second digital encoder 70, attached to shaft 66 in a known manner, which measures the angular displacement of the casing 50 (and thus the transmit laser beam 22) in the y-direction. Thus, the motors 60, 68 provide for panning and tilting of the casing 50.

The output of the first and second encoders 62, 70 is electrically coupled to the computer to provide a feedback loop. The feedback loop is required because the motors 60, 68 are typically coupled to the shafts 54, 66 via respective gearboxes and are thus not in direct contact with the shafts 54, 66. This makes the movement of the casing 50 which is effected by operation of the motors 60, 68 less accurate. However, as the encoders 62, 70 are coupled directly to their respective shafts 54, 66 then the panning and tilting of the casing in the x- and y-directions can be measured more accurately, as will be described.

The embodiment of the image capture and laser transmitter and receiver unit 10 shown in Fig. 2 is slightly different from that illustrated in Fig. 1. The camera within unit 10 is not bore-sighted with the laser, and thus casing 50 is provided with a camera lens 72, a laser transmitter lens 74 and a laser receiver lens 76. It should be noted that the laser transmitter lens 74 and the camera lens 72 may be integrated into a single lens as illustrated in Fig. 1. Ideally, the camera lens 72, laser transmitter lens 74 and laser receiver lens 76 would be co-axial. This could be achieved in practice by mechanically adjusting the lenses 72, 74, 76 to make them co-axial. However, this is a time consuming process and the offsets between the lenses can be calculated and the survey apparatus can be calibrated to take these offsets into account, as will be described. This calibration is generally simpler and quicker than mechanically aligning the lenses 72, 74, 76.

Referring to Fig. 3, there is shown in more detail the apparatus of Fig. 2. It should be noted that the casing 50 which houses the image capture and laser

transmitter and receiver unit 10 is not provided with a separate camera lens (as in Fig. 2). It should also be noted that the casing 50 in Fig. 3 is mounted to facilitate rotational movement in the x-direction, but can be manually tilted in the y-direction.

As can be seen more clearly in Fig. 3, the casing 50 is mounted to the U-shaped yoke 52. The yoke 52 is coupled to the shaft 54 using any conventional means such as screws 80. The shaft 54 is driven by the stepper motor 60 via a worm/wheel drive gearbox 82. The digital encoder 62 is provided underneath a plate 84 through which the shaft 54 passes and to which the gearbox/motor assembly is attached. Plate 84 also includes a rotary gear assembly 86 which is driven by the motor 60 via the worm gearbox 82 to facilitate rotational movement of the shaft 54.

The motor, gearbox and shaft assembly is mounted within an aluminium casing 86, the casing 86 also having a rack 88 mounted therein. The rack 88 contains the necessary electronic circuitry for driving and controlling the operation of the survey apparatus, and includes a stepper motor driver board 90, a laser control board 92 and an interface board 94.

The first and second digital encoders 62, 70 may be of any conventional type, such as Moir Fringe, barcode or mask. Moir fringe type encoders are typically used as they are more accurate. Fig. 4 shows a simplified schematic illustration of a digital encoder, generally designated 110. Encoder 110 typically comprises a casing 112 in which a disc 114 is rotatably mounted. The disc 114 is provided with a pattern and is typically at least partially translucent. The type of pattern defined on the disc 114 determines the type of

encoder.

A light emitting diode (LED) 116 is suspended above the disc 114 and emits a light beam (typically collimated by a lens (not shown) which shines through the disc 114. The light emitted by the LED 116 is detected by a detector, typically a cell array 118. As the disc 114 rotates (in conjunction with the shaft to which it is coupled) a number of electrical outputs are generated per revolution of the disc 114 by the cell array 118 which detects the light passing through the disc 114 from the LED 116. These types of encoders usually have two output channels (only one shown in Fig. 4) and the phase relationship between the two signals can be used to determine the direction of rotation of the disc 114.

The encoder 110 produces a pulse output per unit of revolution. Thus, as the disc 114 rotates, the pattern on the disc 114 causes electrical pulses to be generated by the cell array 118 in response to the pattern on the disc 114. These pulses can be counted and, given that one pulse is proportional to a certain degree of rotation, the angular rotation of the disc 114 and thus the shaft 54 can be calculated.

Fig. 5 shows the survey apparatus 100 (schematically represented in Fig. 5 but shown more clearly in Figs 2 and 3) in use. The apparatus 100 is controlled and operated using software installed on the computer (shown schematically at 120) via a cable 122, telemetry system or other remote or hardwired control. An image of the target is displayed on the computer screen using the camera 32 (Fig. 1) and is schematically shown as image 124 in Fig. 5. When the image 124 of the target area of interest is viewed on the screen, the user of the apparatus 100 instructs the camera 32 (included as

part of the apparatus 100) to take a freeze frame image of the target area. The freeze frame image 124 is a digital image made up of a plurality of pixels and Fig. 6 is a schematic representation of the display produced on the computer screen of the freeze frame image 124. The image 124 is typically divided into an array of pixels, with the image containing, for example, 200 by 200 pixels in the array.

Each pixel within the array has an x and y coordinate associated with it using, for example, the centre C of the picture as a reference point. Thus, each pixel within the digital image can be individually addressed using these x and y co-ordinates.

The individual addresses for each pixel allow the user to select a particular object (for example a tree 126) within the digital image 124. The tree 126 can be selected using a mouse pointer for example, where the mouse pointer is moved around the pixels of the digital image by movement of a conventional mouse provided with the computer in a known manner. The x and y coordinates of each pixel may be displayed on the screen ad the mouse pointer is moved around the image. Clicking the mouse button with the pointer on the tree 126 selects a particular pixel 128 within the array which is identified by its x and y coordinates.

The computer is then used to calculate the horizontal angle H_A and the vertical angle V_A (Fig. 6). The horizontal angle H_A and the vertical angle V_A are the relative angles between the centre point C of the image and the pixel 128, as schematically shown in Fig. 6.

The methodology for calculating the horizontal angle H_A and the vertical angle V_A from the pixel x, y

coordinates is as follows. Fig. 7 is a simplified schematic diagram of inside the camera 32 which shows the camera lens 72 and a charge-coupled device (CCD) array 130. The camera 32 is typically a zoom camera which therefore has a number of focal lengths which vary as the lens 72 is moved towards and away from the CCD array 130.

Referring to Fig. 7, the angles of horizontal and vertical views, or the field of view in the horizontal and vertical direction θ_H, θ_V (θ_V not shown in Fig. 7) can be calibrated and calculated at different focal lengths of the camera 32. For simplicity, it is assumed that the CCD array 130 is square, and thus the field of view in the horizontal and vertical directions θ_H, θ_V will be the same, and thus only the field of view in the horizontal direction θ_H will be considered. The methodology described below considers one zoom position only.

Having calculated (or otherwise obtained) the field of view in the horizontal direction θ_H then the principal distance PD (in pixels) can be calculated. The principal distance PD is defined as the distance from the plane of the lens 72 to the image plane (ie the plane of the CCD array 130).

Referring to Fig. 8, if the image width on the CCD array is defined as H_R, then using basic trigonometry $\tan(\theta_H/2) = H_R/(2PD)$. Thus,

$$PD = H_R/2(\tan(\theta_H/2))$$

If the distance between each pixel in the image 124 in a certain unit (ie millimetres) is known, then the principal distance PD can be converted into a distance

in pixels. For example, if the field of view in the horizontal and vertical angles θ_H, θ_V is, for example 10°, and the image contains 200 by 200 pixels, then moving one twentieth of a degree in the x or y direction is the equivalent of moving one pixel in the x or y direction.

When initially using the apparatus 100, the camera 32 is used to take a calibration freeze frame image and the laser 12 is activated to return the range R to the centre point C of the image. However, the laser axis is typically offset from the camera axis. The horizontal and vertical offsets between the laser axis and the camera axis when the freeze frame image is taken are defined as H_{offset} and V_{offset} and are known. Knowing the range R and the horizontal and vertical offsets H_{offset}, V_{offset} allows the offset horizontal and vertical distances l_x and l_y in terms of pixels to be calculated. Referring to Fig. 9, the centre point C of the image 124 taken by the camera 32 and the laser spot 132 where the transmit laser beam 22 hits the target area is typically offset by the horizontal and vertical distances l_x and l_y.

Fig. 10 is a schematic representation illustrating the horizontal offset H_{offset} outwith the camera 32, and Fig. 11 is a schematic representation illustrating the horizontal distance l_x in terms of pixels, corresponding to H_{offset}, within the camera 32. Referring to Figs 10 and 11 and using basic trigonometry,

$$\tan\theta = H_{offset}/R$$

and,

$$l_x = PD(\tan\theta)$$

Thus,

$$l_x = PD(H_{offset}/R)$$

and it follows that

$$l_y = PD(V_{offset}/R)$$

If the range to a certain object within the target area (such as the tree 126 in Fig. 6) is required, then the computer must calculate the horizontal and vertical angles H_A, H_v through which the casing 50 and thus the laser beam 22 must be moved in order to target the object.

The user selects the particular pixel (relating to the object of interest) within the image using a mouse pointer. In Fig. 12, the selected object is represented by pixel A which has coordinates (x, y), and the laser spot 132 has coordinates (l_x, l_y) calculated using the previous method. The coordinates (x, y) of point A are already known using the coordinates of the pixel array of the image.

If the horizontal distance between pixel A and the laser spot 132 is defined as d_x, and similarly the vertical distance between pixel A and the laser spot 132 is defined as d_y, then

$$d_x = x - l_x$$

and

$$d_y = y - l_y,$$

and it follows that the horizontal and vertical angles H_A, V_A can be calculated as

$$H_A = \text{inverse tan } (d_x/PD)$$

and

$$V_A = \text{inverse tan } (d_y/PD).$$

Referring back to Fig. 2, having calculated the horizontal and vertical angles H_A, V_A through which the casing 50 must be rotated to measure the range to the object A, the computer 120 instructs the motor 60 to pan through an angle of H_A and simultaneously instructs the motor 68 to tilt through an angle of V_A. Thus, the transmit laser beam 22 is directed at the object A selected by the user to determine the range to it.

However, the motors 60, 68 are not directly coupled to the shafts 54, 66 (but via respective gearboxes) and thus can have errors which results in the laser beam 22 not being directed precisely at the object A. However, the encoders 62, 70 can be used to measure more precisely the angles H_A and V_A through which the casing 50 was panned and tilted. If there is a difference between the measured angles H_A and V_A and the angles which were calculated as above, the computer can correct for this and can pan the casing 50 through an angle H_{AC} which is the difference between the calculated angle H_A and the measured angle H_A, and similarly tilt the casing 50 through an angle V_{AC} which is the difference between the calculated angle V_A and the measured angle V_A. The process can then be repeated by using the encoders 62, 70 to check that the casing 50 has been panned and tilted through the angles H_{AC} and V_{AC}. If there is a difference again, then the process can be repeated to further correct for the errors introduced. This iteration process can be continued until the output from the decoders 62, 70 corresponds to the correct angles H_A and V_A. The laser 12 is then fired to give the range to the object A.

The user may then select another object within the

image 124 which is of interest and use the above process to determine the range to that particular object. It should be noted however, that the process to determine the distances l_x and l_y need not be repeated as these distances will be constants.

The apparatus 100 can optionally include a Global Positioning System (GPS) (not shown). The GPS is a satellite navigation system which provides a three-dimensional position of the GPS receiver (in this case mounted as part of the survey apparatus 100) and thus the position of the survey apparatus 100. The GPS is used to calculate the position of the apparatus 100 anywhere in the world to within approximately ± 25 metres. The GPS calculates the position of the apparatus 100 locally using radio/satellite broadcasts which send differential correction signals to ± 1 metre. The GPS can also be used to record the time of all measured data to 1 microsecond.

The apparatus 100 may further include an inclinometer (not shown) and a fluxgate compass (not shown), both of which would be mounted within the casing 50. The fluxgate compass generates a signal which gives a bearing to the target and the inclinometer generates a signal which gives the incline angle to the target. These signals are preferably digitised so that they are in a machine-readable form for direct manipulation by the computer 120.

Thus, in addition to being used to find ranges to specific targets, the survey apparatus may also be used to determine the position of objects, such as electricity pylons, buildings, trees or other man-made or natural structures. The GPS system can be used to determine the position of the apparatus 100 anywhere in

the world, which can be recorded. Optionally, the fluxgate compass within the casing 50 measures the bearing to the target, which can be used to determine the position of the target using the reading from the GPS system and the reading from the fluxgate compass.

It should also be noted that the encoders 62, 70 may be used to determine the bearing to the target instead of the fluxgate compass. In this case, if the encoder is given an absolute reference, such as the bearing to an electricity tower or other prominent landmark which is either known or can be calculated, then the angle relative to the reference bearing can be calculated using the outputs from the encoders 62, 70, thus giving the bearing to the target.

In addition, the position of the apparatus and the calculated position of the target could be overlayed on a map displayed on the computer screen so that the accuracy of the map can be checked. This would also allow more accurate maps to be drawn.

Referring to Fig. 14, there is shown an exemplary image printed from the screen of the computer 120. The survey apparatus 100 of the present invention is advantageously operated remotely. As the apparatus 100 is computer-controlled, remote operation of the system can be achieved via the Internet, a telemetry link or a phone line for example. The survey apparatus 100 is particularly suited to applications where surveying is required in hazardous and/or hostile environments.

Thus, as show in Fig. 14, the screen image may include a sighting graticule 150 which allows the user to select the target with increased accuracy. The orientation of the apparatus 100 can be moved using any

particular control means associated with the computer such as a mouse, joystick or the like. In particular, the apparatus 100 may be moved by the user clicking on a particular target within the image on the screen using a mouse for example. As the apparatus is moved, the camera 32 will display an image on the screen which the user can use to determine the target area.

Thereafter, the apparatus 100 will be activated by pressing a key, clicking a mouse button or by any other conventional means, and the camera 32 will take the freeze frame which will be displayed on the computer screen. The user can then select which target he wishes to range too within the picture using the mouse pointer. This will give the two-dimensional x, y pixel coordinates for the selected object. The computer 120 may then calculate the horizontal and vertical angles H_A, V_A as described above. The computer 120 then instructs the motors 60, 68 to pan and tilt through their respective angles until the laser transmit beam 22 is pointing at the object of interest. This may require the iteration process described above to ensure that the laser beam 22 is accurately aligned with the target object. Once the beam 22 is aligned with the object, the laser 12 will be activated to determine the range R to a particular object. Once the range is known, the screen image can be overlayed with the range and the horizontal and vertical angles H_A, V_A, as indicated generally by 152 in Fig. 14. This information can then be saved for future reference and/or analysis.

The apparatus 100 is particularly suited to applications in hostile and/or hazardous environments. The apparatus 100 can be operated remotely and thus ensures that the user can survey an area of interest

from a relatively safe, remote environment.

The apparatus 100 can be mounted on top of a tripod stand, mounted on a vehicle on a telescopic mast, or on an elevated platform for greater visibility. The apparatus 100 can be used to measure the range to most types of surfaces including earth, coal, rock and vegetation at distance in excess of 1 kilometre (km).

Referring to Figs 15a to c, there is shown a vehicle 160 (such as a tank) which is provided with the apparatus 100 mounted on a telescopic or extendable arm 162. As illustrated in Fig. 15a, the apparatus 100 may be completely retracted when the vehicle 160 is in motion, and may be stored behind an armoured shield 164. The casing 50 of the apparatus 100 would tilt downwards to a horizontal attitude and the telescopic arm 162 would extend so that the apparatus 100 was substantially protected by the armoured shield 164.

When the area to be surveyed is reached, the vehicle is stopped and the apparatus 100 deployed on the telescopic arm 162 by reversing the procedure described above, as illustrated in Fig. 15b. The telescopic arm is preferably mounted on a rotation joint 166 so that the apparatus 100 can be rotated through 360° as indicated by arrow 168 in the enlarged portion of Fig. 15b. A motor 170 is coupled to the rotation joint 166 to facilitate rotation of the joint 166. The apparatus 100 can typically be raised to a height of approximately 15 metres or more, depending upon the construction of the arm 162.

The particular configuration shown in Figs 15a and 15b can accommodate large angles of roll and pitch of the vehicle, such as that shown in Fig. 15c. In Fig. 15c,

the vehicle 160 is stationary on a slope 172 and has been rolled through an angle indicated by arrow 174 in Fig. 15c. The user or the computer can correct for the angle of roll 174 by moving the arm 162 until the inclinometer indicates that the apparatus 100 is level. A level 178 (Figs 16a, 16b) may be provided on the base of the apparatus 100 if required.

Figs 16a and 16b are front and side elevations of the apparatus 100 mounted on the arm 162. As can be seen from Figs 16a and 16b, the arm 162 can be rotated through 360° as indicated by arrow 176 in Fig. 16a. The apparatus 100 is mounted on a pan and tilt head 180 to facilitate panning and tilting of the apparatus 100.

Servo motors within the pan and tilt head 180 pan and tilt the head 180 into the plane of roll and pitch of the vehicle 160 (Fig. 15c). Thereafter, the motors 60, 68 of the apparatus 100 pan and tilt the apparatus 100 until it is level, using the level indicator 178 as a guide.

Further electronic levels (not shown) within the apparatus 100 can measure any residual dislevelement and this can be corrected for in the software before any measurements are taken.

A particular application of the apparatus 100 deployed on a vehicle 160 would be in a military operation. The apparatus 100 can be deployed remotely on the arm 162 and used to survey the area surrounding the vehicle 160. The computer 120 could be provided with a ground modelling software package wherein the user selects a number of key targets within the area using the method described above, and finds the range and bearing to, height of and global position of (if required) these

targets. The software package will then plot these points, including any heights which the GPS 182 (Figs 16a, 16b) can generate, and in-fill or morph the remaining background to produce an image of the terrain, such as that shown in Fig. 17.

Fig. 17 shows an exemplary terrain which has been surveyed, the terrain including a river 190, the river 190 being in a valley with sides 192, 194 raising upwardly from the river 190. Once the ground has been modelled, design templates of equipment carried by the vehicle 160 (or any other vehicle, aircraft etc) can be overlayed over the image to assess which type of equipment is required to cross the obstacle, such as the river 190. The surveying operation can be done discretely and in a very short time compared with conventional survey techniques. Such conventional techniques would typically be to deploy a number of soldiers to survey the area manually and report back. However, with the apparatus 100 deployed on the vehicle 160 the survey can be done quicker, more accurately and more safely, without substantial risk to human life.

It is possible to conduct multiple surveys with the vehicle 160 in one or more locations, with the data from each survey being integrated to give a more accurate overall survey of the surrounding area.

Furthermore, if the arm 162 was disposed at the front of the vehicle 160 as shown in Figs 18a and 18b, the apparatus 100 can be used to check the profile of the ground in front of the vehicle 160. Thus, the profile of the ground could be shown in profile and plan views as illustrated in Figs 19a, and 19b respectively. Alternatively, or additionally, the software on the computer 120 could be used to generate a head-up video

display to which the driver of the vehicle 160 could refer. Fig. 20 illustrates an example of the type of head-up display which could be generated. The heading of the tank (measured by the fluxgate compass) is displayed, with the range to and height of the ground (and any obstructions) in front of the vehicle also being displayed. The height displayed could be the height relative to the vehicles' position, or could be the absolute height obtained from the GPS 182.

Figs 21 to 23 illustrate three further applications of the apparatus 100. Fig. 21 illustrates how to calculate the height between two points A and B (indicated by crosses in Fig. 21). The user will select the points A and B and then measure the range to them using the method described above. This will give three-dimensional coordinates for each point A and B. If it is assumed that the range to each point is approximately equal (which can be checked using the measured ranges) and that the x co-ordinates for each point are approximately equal (this can be done using the display of x, y and z co-ordinates displayed on the screen), then the height from A to B is given by subtracting their respective y coordinates. This can then be displayed within a separate window within the screen, for example.

Fig. 22 illustrates the technique used to measure the height and distance between two points A and B. The range to A and B are first measured using the apparatus 100 as described above. The slope from A to B, the horizontal difference between A and B and the gradient of A to B are then calculated, the results being overlayed on the screen.

Fig. 23 illustrates how a rock face or the like may be

profiled. Range measurements are taken at intervals along the profile (indicated by crosses in Fig. 23). The height of each measurement will be calculated from either the inclinometer reading or can be determined using the GPS 182. Thus, a rock profile may be produced, as shown in Fig. 23.

While the above is a description of the typical applications which the survey apparatus of the present invention may be used for, it will be apparent to those skilled in the art the full range of applications of the survey apparatus disclosed herein, and the present invention is not limited to the examples discussed.

Thus, there is provided a survey apparatus and method which provides for remote control operation using a video camera to relay images back to a host computer in real-time. The image on the host computer allows the user to select particular objects of interest within the surveyed area and measure the range to these objects. The apparatus can also be used to determine rock profiles, heights between two points, the position of certain objects and the like.

Modifications and improvements may be made to the foregoing without departing from the scope of the present invention.

CLAIMS

1. A survey apparatus comprising a range finder, a camera and a processor capable of processing image and range signals, wherein the camera facilitates aiming of the range finder.

2. A survey apparatus according to claim 1, wherein the camera comprises a video camera.

3. A survey apparatus according to either preceding claim, wherein the camera comprises a digital camera.

4. A survey apparatus according to any preceding claim, wherein the apparatus includes a display device to allow a user of the apparatus to view a target area using the camera.

5. A survey apparatus according to claim 4, wherein the display device comprises a VGA monitor.

6. A survey apparatus according to any preceding claim, wherein the processor comprises a computer.

7. A survey apparatus according to any preceding claim, wherein the range finder comprises a laser range finder.

8. A survey apparatus according to any preceding claim, wherein the range finder is bore-sighted with the camera.

9. A survey apparatus according to any preceding claim, wherein the apparatus includes a pan and tilt unit for panning and tilting of the range finder and/or camera.

10. A survey apparatus according to claim 9, wherein the pan and tilt unit comprises a first motor for panning of the range finder and/or camera, and a second motor for tilting of the range finder and/or camera.

11. A survey apparatus according to either claim 9 or claim 10, wherein operation of the first and second motors is controlled by the processor.

12. A survey apparatus according to any one of claims 9 to 11, wherein the pan and tilt unit includes first and second digital encoders for measuring the angles of pan and tilt.

13. A survey apparatus according to claim 12, wherein the outputs of the first and second encoders are fed to the processor.

14. A survey apparatus according to claim 13, wherein a feedback loop is provided wherein the motors are capable of being operated to pan and tilt the range finder and/or camera through the generated horizontal and vertical angles, and the encoders are capable of verifying the angles moved to verify that the range finder and/or camera were panned and tilted through the correct angles.

15. A survey apparatus according to any one of claims 12 to 14, wherein the first and second encoders are used to calculate the bearing to the target.

16. A survey apparatus according to according to any preceding claim, wherein the image is digitised.

17. A survey apparatus according to claim 16, wherein the image comprises a plurality of pixels.

18. A survey apparatus according to claim 17, wherein the reference point comprises a pixel within the target area.

19. A survey apparatus according to any preceding claim, wherein the reference point comprises a centre point of the target area.

20. A survey apparatus according to any one of claims 16 to 19, wherein the target is selected by selecting a pixel within the target.

21. A survey apparatus according to any preceding claim, wherein the survey apparatus includes a compass and an inclinometer and/or gyroscope.

22. A survey apparatus according to claim 21, wherein the compass comprises a digital fluxgate compass.

23. A survey apparatus according to either claim 21 or claim 22, wherein signals from the compass, inclinometer and/or gyroscope are processed to provide data to the processor.

24. A survey apparatus according to any preceding claim, wherein the survey apparatus further includes a position fixing system for identifying the geographical position of the apparatus.

25. A survey apparatus according to claim 24, wherein the position fixing system comprises a Global Positioning System.

26. A survey apparatus according to claim 25, wherein the Global Positioning System includes a Differential Global Positioning System.

27. A survey apparatus according to either one of claims 24 to 26, wherein the signal from the position fixing system is processed to provide data to the processor.

28. A survey apparatus according to any preceding claim, wherein the survey apparatus is mounted on a mounting device.

29. A survey apparatus according to claim 28, wherein the mounting device comprises a tripod stand.

30. A survey apparatus according to any preceding claim, wherein the apparatus can is mounted on an elevating platform, telescopic elevating tube, telescopic arm or robotic arm.

31. A survey apparatus according to claim 30, wherein the elevating platform, telescopic elevating tube, telescopic arm or robotic arm is capable of 360° rotation.

32. A survey apparatus according to either claim 29 or claim 30, wherein the elevating platform, telescopic elevating tube, telescopic arm or robotic arm is mounted on a vehicle.

33. A survey apparatus according to claim 32, wherein the apparatus allows data gathering from within the vehicle to construct a digital terrain model of the terrain surrounding the vehicle.

34. A method of measuring the range to a target, the method comprising the steps of

providing a camera to view a target area;

providing a range finder;

using the camera to produce an image of the target area;

selecting the target within the target area;

generating horizontal and vertical angles between a reference point and the target; and

moving the range finder and/or camera, if required, through the generated horizontal and vertical angles to measure the range to the target.

35. A method according to claim 34, wherein the camera comprises a video camera.

36. A method according to either claim 34 or claim 35, wherein the camera comprises a digital camera.

37. A method according to any preceding claim, wherein the apparatus includes a display device to allow a user of the apparatus to view a target area using the camera.

38. A method according to claim 37, wherein the display device comprises a VGA monitor.

39. A method according to any one of claims 34 to 38, wherein the processor comprises a computer.

40. A method according to any one of claims 34 to 39, wherein the range finder comprises a laser range finder.

41. A method according to any one of claims 34 to 40, wherein the range finder is bore-sighted with the camera.

42. A method according to any one of claims 34 to 41, wherein the image is digitised.

43. A method according to claim 42, wherein the image comprises a plurality of pixels.

44. A method according to claim 43, wherein the reference point comprises a pixel within the target area.

45. A method according to any one of claims 34 to 43, wherein the reference point comprises a centre point of the target area.

46. A method according to any one of claims 42 to 45, wherein the target is selected by selecting a pixel within the target.

47. A method according to claim 46, wherein the target pixel is selected using a mouse pointer.

48. A method according to any one of claims 34 to 47, wherein the method comprises the further steps of

obtaining a focal length of the camera;

obtaining a field of view of the camera;

calculating the principal distance of the camera;

obtaining the horizontal offset and vertical offset between an axis of the camera and an axis of the laser;

calculating the horizontal and vertical offsets in terms of pixels;

calculating the difference between the horizontal and vertical offsets in terms of pixel and the x and y coordinates of the target pixel; and

calculating the horizontal and vertical angles.

49. A method according to any one of claims 34 to 48, wherein the apparatus includes a pan and tilt unit for panning and tilting of the range finder and/or camera.

50. A method according to claim 49, wherein the pan and tilt unit comprises a first motor for panning of the range finder and/or camera, and a second motor for tilting of the range finder and/or camera.

51. A method according to either claim 49 or claim 50, wherein operation of the first and second motors is controlled by the processor.

52. A method according to any one of claims 49 to 51, wherein the pan and tilt unit includes first and second digital encoders for measuring the angles of pan and tilt.

53. A method according to claim 52, wherein the outputs of the first and second encoders is fed to the processor.

54. A method according to claim 53, wherein a feedback loop is provided wherein the motors are operated to pan and tilt the range finder and/or camera through the generated horizontal and vertical angles, and the encoders are used to check the angles to ensure that the range finder and/or camera were panned and tilted through the correct angles.

55. A method according to any one of claims 48 to 54, the method comprising the further steps of

instructing the pan and tilt unit to pan and tilt the range finder and/or camera through the vertical and horizontal angles;

measuring the horizontal and vertical angles using the encoders;

verifying that the angles through which the range finder and/or camera are moved is correct;

obtaining horizontal and/or vertical correction angles by subtracting the measured horizontal and vertical angles from the calculated horizontal and vertical angles;

adjusting the pan and tilt of the range finder and/or camera if necessary; and

firing the range finder to obtain the range to the target.


10
12
14
18
20
34
32
24
22
Tx
Rx
26
28
16
30

Fig. 1


64
58
72
68
50
100
66
70
68
74
76
52
62
54
60
56

Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10



Fig. 11



Fig. 12



Fig. 13



Fig. 14



Fig. 15a



Fig. 15b



Fig. 15c



Fig. 16a



Fig. 16b



Fig. 17

Fig. 18a



Fig. 18b





Fig. 19a



Fig. 19b



Fig. 20



Fig. 21



Fig. 22



Fig. 23

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 99/01361

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G01C15/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 G01C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 481 278 A (PIETZSCH IBP GMBH) 22 April 1992 (1992-04-22)	1,4-7, 9-14,34, 37-40, 49-54
Y	column 4, line 17 - line 23	21, 23-25, 27,28, 30,32,33
	column 5, line 28 - column 7, line 11; figures	
Y	US 5 077 557 A (INGENSAND HILMAR) 31 December 1991 (1991-12-31)	21, 23-25, 27,28
	column 2, line 4 - line 17; figures	

-/--

[X] Further documents are listed in the continuation of box C.

[X] Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
19 August 1999	26/08/1999

Name and mailing address of the ISA	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Hoekstra, F

1

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 99/01361

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 379 045 A (GILBERT CHARLES ET AL) 3 January 1995 (1995-01-03) column 9, line 51 - column 10, line 4 column 13, line 1 - line 6; figures 1,2	30,32,33
X	EP 0 661 519 A (TOPCON CORP) 5 July 1995 (1995-07-05) the whole document	1,3-6, 8-13, 34-39, 41,45, 49-53

1

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/GB 99/01361

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0481278 A	22-04-1992	DE 4032657 A	16-04-1992
		DE 9007731 U	10-11-1994
US 5077557 A	31-12-1991	CH 674898 A	31-07-1990
		AT 85703 T	15-02-1993
		WO 9000718 A	25-01-1990
		EP 0403585 A	27-12-1990
		JP 2874776 B	24-03-1999
		JP 3500334 T	24-01-1991
US 5379045 A	03-01-1995	WO 9506883 A	09-03-1995
EP 0661519 A	05-07-1995	JP 7198383 A	01-08-1995
		CN 1110399 A	18-10-1995
		EP 0874218 A	28-10-1998